6-14-04; 5:16PM; :19496600809 # 4/ 1

Application No.: 09/709,800 Docket No.: JCLA6349

In The Claims:

Claims 1-2 (Cancelled)

Claim 3. (Currently amended) The apparatus for processing data of claim 1, An apparatus

for processing data, said apparatus comprising:

a special register bank of N-bit data processing registers;

a general register bank of N-bit data processing registers;

a selector, coupled to the special register bank and the general register bank, for selecting

one of the special and general register banks and outputting a selected N-bit result from the

selected register bank in according to a class signal received by the selector, wherein the selected

N-bit result and a N-bit data form a 2N-bit addition operand; the selector further receiving a class

signal, wherein the selector selects one of the special and general register banks in response to

the class signal

a multiplier for performing multiply operation upon a first operand and a second operand

and outputting an 2N-bit multiplied result; and

one accumulator, coupled to the multiplier, the selector and the general register bank, for

performing accumulate operation upon the 2N-bit multiplied result and the 2N-bit addition

operand and outputting a 2N-bit accumulated result.

Claim 4. (original) The apparatus for processing data of claim 3, the class signal is used

for indicating a first class of instruction or a second class of instruction, wherein the first class of

Page 2 of 9

6-14-04; 5:16PM; ;19496600809 # 5/ 1

Application No.: 09/709,800

Docket No.: JCLA6349

instruction is executing a first calculation of $N*N+2N\rightarrow 2N$ and the second class of instruction is executing a second calculation of $N*N+N\rightarrow N$.

Claim 5. (original) The apparatus for processing data of claim 4, the apparatus further comprising a detecting device, coupled to the accumulator, for receiving the 2N-bit accumulated result and for checking if a case of overflow occurs.

Claim 6. (currently amended) The apparatus for processing data of claim 5, wherein the outputted N-bit result from the selector and the N-bit data held in the general register bank are formed in combination as a first N-bit part and a second N-bit part of the 2N-bit addition operand,

the accumulated result includes a third N-bit part and a fourthforth N-bit part,

when the class signal is the second class of instruction, the detecting device comparing the first N-bit part of the 2N-bit addition operand and the third N-bit part of the accumulated result to determine if the case of overflow occurs.

Claim 7. (Currently amended) The apparatus for processing data of claim 31, the apparatus further comprising a detecting device, coupled to the accumulator, for receiving the 2N-bit accumulated result and for checking if a case of overflow occurs.

Claim 8. (Currently amended) The apparatus for processing data of claim 7, wherein the outputted N-bit result from the selector and the N-bit data are formed in combination as a first N-bit part and a second N-bit part of the 2N-bit addition operand,

Page 3 of 9

6-14-04; 5:16PM; :19496600809 # 6/ 19

Application No.: 09/709,800

Docket No.: JCLA6349

the accumulated result includes a third N-bit part and a fourthforth N-bit part,

when the class signal is the second class of instruction, the detecting device comparing the first N-bit part of the 2N-bit addition operand and the third N-bit part of the accumulated result to determine if the case of overflow occurs.

Claims 9-10 (Cancelled)

Claim 11. (Currently amended) The method for processing data of claim 10, A method for processing data using an apparatus having a special register bank of N-bit data processing registers, a general register bank of N-bit data processing registers, a selector, a multiplier and an accumulator, the method comprising:

selecting one of the special and general register banks and outputting a N-bit result from the selected register bank in according to a class signal received by the selector, wherein the N-bit result and a N-bit data form a 2N-bit addition operand; wherein the step of selecting one of the special and general register banks and outputting N-bit data from the selected register banks further comprising a step of receiving a class signal is determined by a class signal received by the selector

performing multiply operation upon a first operand and a second operand and outputting
an 2N-bit multiplied result; and

performing accumulate operation upon the 2N-bit multiplied result and the 2N-bit addition operand by one accumulator and outputting a 2N-bit accumulated result.

Page 4 of 9

6-14-04; 5:16PM; ;19496600809 # 7/ 1

Application No.: 09/709,800

Docket No.: JCLA6349

Claim 12. (original) The method for processing data of claim 11, the class signal is used for indicating a first class of instruction or a second class of instruction, wherein the first class of instruction is executing a first calculation of $N*N+2N\rightarrow 2N$ and the second class of instruction is executing a second calculation of $N*N+N\rightarrow N$.

Claim 13. (original) The method for processing data of claim 12, further comprising a step of receiving the 2N-bit accumulated result and checking if a case of overflow occurs.

Claim 14. (currently amended) The method for processing data of claim 13, wherein the outputted N-bit result from the selector and the N-bit data held in the general register bank are formed in combination as a first N-bit part and a second N-bit part of the 2N-bit addition operand,

the accumulated result includes a third N-bit part and a fourthforth N-bit part,

when the class signal is the second class of instruction, comparing the first N-bit part of the 2N-bit addition operand and the third N-bit part of the accumulated result to determine if the case of overflow occurs.

Claim 15. (original) The method for processing data of claim 9, further comprising a step of receiving the 2N-bit accumulated result and checking if a case of overflow occurs.

Claim 16. (currently amended) The method for processing data of claim 15, wherein the outputted N-bit result from the selector and the N-bit data are formed in combination as a first N-bit part and a second N-bit part of the 2N-bit addition operand,

Page 5 of 9

6-14-04; 5:16PM; :19496600809 # 8/ 11

Application No.: 09/709,800 Docket No.: JCLA6349

the accumulated result includes a third N-bit part and a fourthforth N-bit part,

when the class signal is the second class of instruction, comparing the first N-bit part of the 2N-bit addition operand and the third N-bit part of the accumulated result to determine if the case of overflow occurs.